

# Material Safety Data Sheet



## U.S. Department of Labor

Occupational Safety and Health Administration

OSHA's Hazard Communication  
Standard,

29 CFR 1910.1200. Standard must be  
consulted for specific requirements.

### NUFREE NUDESSE BOTANICAL HAIR REMOVER

Form Approved

OMB No. 1218-0072

EQUIBAL, INC.	Emergency Telephone Number 845-726-4494 – 1-800-247-2405
63-65 Jersey Avenue, PO Box 180	Telephone Number for Information 845-726-4494
Unionville, NY 10988	Date Prepared 8/15/99
USA	

#### Section II - Hazard Ingredients/Identity Information

Boiling Point	>707 F	Specific Gravity (H <sub>2</sub> O = 1)	.8
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water SEMI SOLID			
Appearance and Odor OPAQUE SEMI SOLID WITH SLIGHT SOYBEAN CHARACTERISTIC ODOR			

#### Section IV - Fire and Explosion Hazard Data

None	OSHA 174, Sept. 1985
------	----------------------

#### Section V - Reactivity Data

	Inhalation? NA	Skin? Remove with vegetable oil.	Ingestion? Drink plenty of water.
Health Hazards ( <i>Acute and Chronic</i> ) NONE KNOWN			
COSMETIC DISPERSION WITH CHARACTERISTIC ODOR – SOYA DERIVITIES			

Signs and Symptoms of Exposure	N/A
Medical Conditions	Generally Aggravated by Exposure NONE KNOWN
Emergency and First Aid Procedures:	Flush eyes with plenty of cool water. Do Not Rub.

**Section VII - Precautions for Safe Handling and Use**

Respiratory Protection ( <i>Specify Type</i> )		NA
Ventilation	Local Exhaust	✓
		Use absorbent material to collect for disposal. Dispose of in accordance with Federal, State and local Regulations.
Page 2		* U.S.G.P.O.: 1986 - 491 - 529/45775

Material Safety  
Data Sheet



U.S. Department of Labor

Occupational Safety and Health Administration

OSHA's Hazard Communication  
Standard,

29 CFR 1910.1200. Standard must be  
consulted for specific requirements.

**NUFREE ERASING LOTION**

Form Approved

OMB No. 1218-0072

Manufacturer's Name <b>EQUIBAL, INC.</b>	Emergency Telephone Number 845-726-4494 -- 1-800-247-2405
63-65 Jersey Avenue, PO Box 180	Telephone Number for Information 845-726-4494
Unionville, NY 10988	Date Prepared 1/25/01
USA	Signature of Preparer (optional)

**Section II - Hazard Ingredients/Identity Information**

Boiling Point	>707 F	Specific Gravity (H <sub>2</sub> O = 1)	0.818 at 16°F
Vapor Pressure (mm Hg.)	<1mm Hg at 20°C	Melting Point	ND
Vapor Density (AIR = 1)	ND	Evaporation Rate (Butyl Acetate = 1)	ND
Solubility in Water WATER SOLUABLE			
Appearance and Odor SLIGHTLY YELLOW CLEAR OILY LOTION.			

**Section IV - Fire and Explosion Hazard Data**

Flashpoint: 435°F Pinsky Mortons -- Not Flammable	OSHA 174, Sept. 1985
Extinguishing Media: Agents approved for Class B (Dry Chemicals, carbon Dioxide, Foam or Steam) or water fog. Firefighters should wear usual equipment and positive self contained breathing apparatus.	

**Section V - Reactivity Data**

Stable. Avoid contact with very strong oxidizing agents.		Skin? Wash skin with soap and water. Flush eyes with cool water.	Ingestion? If ingested, drink plenty of water.
--	--	--	---

Health Hazards ( <i>Acute and Chronic</i> )	NONE KNOWN
COSMETIC EMULSION WITH LITTLE TO NO CHARACTERISTIC ODOR	
Signs and Symptoms of Exposure	N/A
Medical Conditions Generally Aggravated by Exposure NONE KNOWN	
Emergency and First Aid Procedures Wash skin with soap and water. Flush eyes with cool water. If swallowed, drink plenty of water. Seek medical attention if symptoms persist.	

**Section VII - Precautions for Safe Handling and Use**

Respiratory Protection ( <i>Specify Type</i> ) ND		
Ventilation	Local Exhaust <input checked="" type="checkbox"/>	Special STORE AT ROOMTEMPERATURE BETWEEN 10°C and 50°C
	Prevent spreading with absorbent Materials. Keep out of waterways.	Use absorbent material to collect for disposal. Dispose of in accordance with Federal, State and local Regulations.
Page 2		* U.S.G.P.O.: 1986 - 491 - 529/45775

# Material Safety Data Sheet



**U.S. Department of Labor**

Occupational Safety and Health Administration

OSHA's Hazard Communication  
Standard,

**FINIPIL**

29 CFR 1910.1200. Standard must be  
consulted for specific requirements.

Form Approved

OMB No. 1218-0072

Manufacturer's Name <b>EQUIBAL, INC.</b>	Emergency Telephone Number 845-726-4494 – 1-800-247-2405
63-65 Jersey Avenue, PO Box 180	Telephone Number for Information 845-726-4494
Unionville, NY 10988	Date Prepared 1/25/01
USA	Signature of Preparer (optional)

## Section II - Hazard Ingredients/Identity Information

Boiling Point	>220°F	Specific Gravity (H <sub>2</sub> O = 1)	1.0 – 1.2
Vapor Pressure (mm Hg.)	ND	Melting Point	ND
Vapor Density (AIR = 1)	ND	Evaporation Rate (Butyl Acetate = 1)	ND
Solubility in Water WATER DISPERSIBLE			
Appearance and Odor WHITE CREAM			

## Section IV - Fire and Explosion Hazard Data

None	OSHA 174, Sept. 1985
------	----------------------

## Section V - Reactivity Data

Stable. <input checked="" type="checkbox"/>		Skin? Wash skin with soap and water. Flush eyes with cool water.	Ingestion? If ingested, drink plenty of water.
Health Hazards (Acute and Chronic)		NONE KNOWN	

COSMETIC EMULSION WITH CHARACTERISTIC ODOR

Signs and Symptoms of Exposure N/A

Medical Conditions  
Generally Aggravated by Exposure NONE KNOWN

Emergency and First Aid Procedures  
Wash skin with soap and water. Flush eyes with cool water. Do not rub eyes. If ingested, drink plenty of water. Seek medical attention if symptoms persist.

**Section VII - Precautions for Safe Handling and Use**

Respiratory Protection ( <i>Specify Type</i> ) NA		
Ventilation	Local Exhaust <input checked="" type="checkbox"/>	Special STORE AT ROOM TEMPERATURE BELOW 85°F
		Use absorbent material to collect for disposal. Dispose of in accordance with Federal, State and local Regulations.
Page 2		* U.S.G.P.O.: 1986 - 491 - 529/45775

Material Safety  
Data Sheet



U.S. Department of Labor

Occupational Safety and Health Administration

OSHA's Hazard Communication Standard,  
29 CFR 1910.1200. Standard must be consulted for specific requirements.

**NUFREE APPLICATOR CLEANING SOLUTION**

Form Approved  
OMB No. 1218-0072

Manufacturer's Name <b>EQUIBAL, INC.</b>	Emergency Telephone Number 845-726-4494 – 1-800-247-2405
63-65 Jersey Avenue, PO Box 180	Telephone Number for Information 845-726-4494
Unionville, NY 10988	Date Prepared 11/01/2011
USA	Signature of Preparer ( <i>optional</i> )

**Section II - Hazard Ingredients/Identity Information**

Boiling Point	>270°C	Specific Gravity (H <sub>2</sub> O = 1)	0.818 at 20°C
Vapor Pressure	< 0.1hPa at 20°C	Melting Point	ND
Vapor Density (AIR = 1)	ND	Evaporation Rate (Butyl Acetate = 1)	ND
Solubility in Water Negligible			
Appearance and Odor Off White CLEAR OIL with slight citrus odor			

**Section IV - Fire and Explosion Hazard Data**

Flashpoint: : >170* C Method: ASTM D93 Upper explosion: not determined Lower explosion: Not determined	OSHA 174, Sept. 1985
Extinguishing Media: Agents approved for Class B (Dry Chemicals, carbon Dioxide, Foam or Steam) or water fog. Firefighters should wear usual equipment and positive self contained breathing apparatus. Do not use water jet.	

**Section V - Reactivity Data**

Stable. Avoid contact with very strong oxidizing agents.	Skin: Wash skin with soap and water. Flush eyes with cool water.	Ingestion: If ingested, drink plenty of water. Do not induce vomiting
--	--	---

Health Hazards ( <i>Acute and Chronic</i> )	NONE KNOWN	
Off White clear oil with slight citrus fragrance.		
Composition Ingredient Information		
White Mineral Oil	99.0%	H304
Triclosan	0.1	
Fragrance	0.1	
Signs and Symptoms of Exposure	N/A	
Medical Conditions	Generally Aggravated by Exposure Aspiration as mist	
Emergency and First Aid Procedures	Wash skin with soap and water/Rinse well. Flush eyes with cool water. If swallowed, drink plenty of water, do not induce vomiting. Seek medical attention if symptoms persist.	

**Section VII - Precautions for Safe Handling and Use**

Respiratory Protection ( <i>Specify Type</i> ) ND		
Ventilation	Local Exhaust ✓	Special STORE AT ROOMTEMPERATURE BETWEEN 10°C and 50°C
	Prevent spreading with absorbent Materials. Keep out of waterways.	Use absorbent material to collect for disposal. Dispose of in accordance with Federal, State and local Regulations.
Page 2		* U.S.G.P.O.: 1986 - 491 - 529/45775